

PROFF WOODCARE HIGH SOLID PROFF OIL



www.proffwoodcare.com

AREAS OF APPLICATION:

Proff Woodcare High Solid Proff Oil is used for basic finish of wood floors in commercial areas with high traffic. It produces a strong and wear resistant surface with enhancement of the wood grain. High Solid Proff Oil natural produces a golden colour whereas white enhances the light colour of oak, ask, pine wood.

APPLICATION OF MATERIAL:

Apply approximately one full coat of High Solid Proff Oil to 12 to 15 square metres of wood floor lengthwise of the wood grain with a paint roller. Use a floor machine with beige or red pad to work the oil into the wood grain.

FINISH:

Proff Woodcare High Solid Proff Oil produces a beautiful satin matt finish which can be maintained and repaired easily. The oiled floor may cleaned with Proff Woodcare Proff Soap, Wood Floor Soap or Oil Refresher. For re-oiling we recommend Maintenance Oil or Maintenance Paste. An oiled floor is highly durable and easy to care for.

- * Ensures that light wood species remain light
- * Easy cleaning with Wood Floor Soap natural or white
- * Suitable for all wood species
- * Suitable for large commercial areas with high frequency of use

- In natural and white
- For oiling of wood floors in commercial areas
- For basic finish with floor machine
- Suitable for all wood species



PROFF WOODCARE HIGH SOLID PROFF OIL



www.proffwoodcare.com

HOW TO DO

High Solid Proff Oil is suitable for use on all untreated interior floors and woodwork in general. High Solid Proff Oil offers a strong protection against fluids and dirt and produces a hard wearing surface. High Solid Proff Oil may be applied only with a floor machine. The wood may be primed with one of the lye primers before the application of High Solid Proff Oil. High Solid Proff Oil natural enhances the natural grain of the wood whereas High Solid Proff Oil white lends a white wash finish either to pine or oak enhancing also the natural grain. High Solid Proff Oil is a fast drying oil. Apply oil to sections of approx. 20 m² at the time. This allows enough time to work the oil well inside the wood grain.

Work Instruction:

1. Make sure that the floor is freshly sanded and cleaned with Intensive Wood Cleaner. Ensure that the floor is completely dry before starting the application of the oil. Moisture in wood should not exceed 12% relative moisture content.
2. Shake the bottle and ensure that all white pigments are evenly distributed in material before application.
Apply 1 litre of oil to approx. 20 m² of floor with a short haired paint roller or brush. Let the oil penetrate the wood grain for up to 15 min. and if dry spots appear, reapply oil. Now work the oil into the wood grain with floor machine mounted with beige or red pad.
3. If not all oil could be worked into the wood grain, remove this excess oil onto the next section of the floor or remove with cotton cloths. Continue in this way till complete area has been coated.
4. Now buff the complete area with a white pad under floor machine.
5. After a 6 hour pre-drying of the area, buff the whole area again with white pad under the machine possibly with a small application of oil to ensure a perfect finish of the wood.
6. Leave the oiled area to dry for 24 hours. Do not expose the floor to water during drying time. After 12 hours, the floor may be used with caution. Cover walkways with corrugated paper.
7. Use Proff Woodcare Wood Floor Soap or Proff Woodcare Oil Refresher mixed with water for regular cleaning. For later maintenance, apply Proff Oil natural or white.

Risk of self ignition: Sanding dust and oil wetted cloths and pads must be disposed of either by soaking in water or burnt immediately after use. Risk of self ignition.

Disposal: Residues and containers are disposed of in accordance with local government regulations.